



FICHA TÉCNICA

R-Cerex Acrylic Wax for floors



CHARACTERÍSTICS:

This product gives to surfaces an immediate and long lasting shine, effortlessly and with great ease of maintenance. It is slip-resistant, and protects surfaces from use. It can be washed with mild detergent. Applicable in terracotta tiles, mosaics, bricks, vinyl, marble and other stone variety.

USAGE:

Applicable in cement tiles, bricks, vinyl, marble and various other stones.

SURFACE PREPARATION:

Wash the surface and let dry thoroughly. If the floor is waxed, remove the old wax.

HOW TO USE

Apply 2 layers of R-Cerex with a clean cloth or mop of cotton, homogeneously and without rubbing, with intervals of 20 minutes. Ensure that the previous layer is completely dry before applying the next. The brightness immediately arises.

MAINTENANCE:

Clean regularly with a _ feather duster or vacuum cleaner. When the waxed surface shows signs of wear, apply a new layer of R-Cerex.

COLOUR:

Colourless and red.

EFFICIENCY:

Approx. 35 m² per Lt. (2 layers)

Vale de Mealhas, Caixa Postal 705-Z, 8150-046 São Brás de Alportel -Algarve- Portugal
Telf: 289 843 555• Email: info@terracotadoalgarve.com • Web: www.terracotadoalgarve.com



FICHA TÉCNICA

TECHNICAL DATA:

- Appearance/coulour:	Liquid, Opaque White or Opaque Red
- Odor:	Typical
- ph:	7,0 – 8,0
- Solubility:	
Water solubility:	Slightly soluble in water
Lipossolubility:	Soluble in most organic solvents
- Relative Density / g/cm ³	1,002 ± 0,01
- Boiling point:	95 °C

COMPOSITION:

Aqueous dispersion of styrene-acyl waxes; perfumed

RISK SYMBOLS:

Not classified as dangerous.

SECURITY INFORMATION:

Wash hands after use. In case of contact with eyes, rinse immediately with water and consult a doctor. If swallowed consult the Poisons Information Centre by phone. Keep out of reach of children. For more detailed information consult the Material Safety Data Sheet.

STORING:

Store product in original containers closed and in a cool, dry place. Store away from heat, light incidence and avoid extreme humidity. After usage maintain it vertically, fully covered, preventing leakage.

PRESENTATION:

Bottles of 1Lt
Churns of 5Lt and 25Lt

OTHER INDICATIONS:

We guarantee the quality of our products. The recommendations and technical information given in this technical sheet are based on laboratory tests and practical experiences. Due to large variations of materials and conditions of application, we ask that you carry out your own tests by following our indications and directions in order to avoid misconceptions and damages that we are naturally not responsible