



Zorpit-BAR Acrylic Cover for the Floor

DESCRIPTION:

-Acrylic resin coating in high capillary penetration surfaces, it is easy to clean and gives them an extraordinary protection.

-Colours: Grey, green, red and transparent.

APPLICATIONS:

-It can be applied in concrete and terrazzo floors to maintain an easy, thorough cleaning. It has an excellent appearance.

-Especially for industrial sheds, houses, garages, cabins villas, warehouses, etc..

-Its good weather resistance allows its use outdoors.

MODO DE EMPREGO E DOSEAMENTO:



PROPRIEDADES

-Ver o quadro de dados técnicos.

Surface: Surface must be cleaned, dry and free of dust and grease.

On tiles it is recommended to first apply a of waterproofing.

Metal surfaces must be free of rust

Product: Stir well before use. Can be applied with a brush or a paint roller, although the application with a large brush allows a better finish as it spreads the product more evenly.

PRECAUTIONS:

Product-Highly flammable, do not smoke while handling. Wear safety glasses, gloves and protective mask

-Follow local and national regulations To waste disposal.

CHARACTRISTICS – TECHNICAL INFORMATION

	BAR-TRANSPARENT	BAR-COLOUR
Appearance	Colourless bright liquid	Coloured bright
Presentation	Monocomponent	Monocomponent
Density	Approx. 0,90-0,95 gr/crr 3	Approx. 0,95-1,00 gr/crr 3
Application Temperature	Approx. between 5º C e 30º C	Approx. between 5º C e 30º C
temperature Resistance	Approx. between 10º C e 60º C	Approx. between 10º C e 60º C
Drying time for the second layer(2º C)	Approx. between 4-6H	Approx. between 4-6H
Final Drying time (2º C)	Approx. 24 H	Approx. 24 H

This Technical data sheet, such as recommendations and information given serves only to describe, Usagee and product applications. The data and information provided are based on our expertise, laboratory tests and practical experience. The recommended dosages are based on our own experience, but however these may vary according to the different usgae conditions. Actual measurements should be determined in the work itself through pretests and are the sole responsibility of the customer. Product usage that is not adjusted to the recommended is not of our responsibility. Our technical service will be at your disposal for any further advice. There is a safety sheet available.

This document cancels the previous editions. Date of last update: 04/06/2009